

# ThinAir<sup>®</sup> HAND DRYER



**SURFACE MOUNTED. ADA-COMPLIANT.**

## NEW ENHANCED STANDARD FEATURES



Adjustable Speed and  
Sound Control



Multi-Voltage Options:  
110-120V, 208-277V



Adjustable Heat Settings -  
High, Medium, Low & Off



Externally Visible  
Service LED

**14**  
**SECONDS\***  
dry time

**95%**  
**COST SAVINGS**  
versus paper towels

**80%**  
**LESS ENERGY**  
than conventional dryers



# ThinAir® HAND DRYER



MODELS: TA - ABS SB -VOLTAGE (See Chart)



**DRY TIME: 14 SECONDS\***

**ENERGY PER USE: 3.7 Wh\***

## FEATURES & BENEFITS

- ✓ 14 Second Dry Time\*
- ✓ Wattage: 950 Watts (Heat On) - 300 Watts (Heat Off)
- ✓ Meets 4" ADA protrusion guidelines to accommodate the visually impaired
- ✓ Adjustable Speed and Sound Control
- ✓ Adjustable Heat Control - High, Medium, Low and Off
- ✓ Washable Pre-Filter
- ✓ 5-Year Limited Warranty
- ✓ Externally Visible Service LED

## COVER OPTIONS

## OPTIONAL ACCESSORIES

- ✓ Microban® Antimicrobial Wall Guards:
  - 89W (White)
  - 89B (Black)
  - 89S (Brushed Stainless Steel)

### TA-ABS

White Polymer (ABS)  
With SanaFor™ Antimicrobial Additive



**TA-ABS**  
White Polymer (ABS)



**TA-SB**  
Brushed Stainless Steel

## OVERALL DIMENSIONS

Width: 9 5/32" (233 mm) Height: 13 15/16" (354 mm) Depth: 4" (102 mm)

## WEIGHT

TA-ABS, SB: 8 lbs. (3.6 kgs.)

## ELECTRICAL

Units are Single Phase; 950 Watts or as low as 300 Watts (without heat) and available as specified in:

| VOLTS    | AMPS   | WATTS    | NO HEAT AMPS | NO HEAT WATTS | HERTZ    |        |
|----------|--------|----------|--------------|---------------|----------|--------|
| 110-120V | 7-7.7A | 770-915W | 3-3.2A       | 310-370W      | 50/60 Hz | cUL US |
| 208-277V | 3.6-4A | 735-950W | 1.5-1.9A     | 300-375W      | 50/60 Hz | cUL US |
| 230V     | 3.9A   | 890W     | 1.7A         | 375W          | 50 Hz    | CE     |

## ACTIVATION

Automatic Sensor Activated

## MOUNTING

Surface-Mounted

## ADA COMPLIANCE

ADA guidelines state that fixtures mounted above 27" must not protrude more than 4" from the wall.

4"




Maximum: 48"  
Recommended: 37"

37"

## SUGGESTED MOUNTING HEIGHTS from floor to bottom of dryer:

|                |              |
|----------------|--------------|
| Men            | 45" (114 cm) |
| Women          | 43" (109 cm) |
| Teenagers      | 41" (104 cm) |
| Small Children | 35" (89 cm)  |
| Accessible     | 37" (94 cm)  |



\*Dry time and energy use testing performed by SGS International on standard Thin Air Hand Dryers to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.



UL Environment published the first global Product Category Rules (PCR) for Hand Dryers and Excel Dryer is proud to have been selected to chair the project. The PCR created evaluation methods through industry consensus that compare products' environmental impact and performance. Third party testing results then enable specifiers and buyers to make a true apples-to-apples comparison of products and more informed decisions.



RoHS



# TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

SEPT  
2016

16TAS0005