

Purpose:

Designed to shield your wall from moisture beneath any hand dryer. The brushed stainless steel brings a modern and clean look while providing effective results.



Construction:

The Splash Guard is fabricated of 20 gauge stainless steel, #4 satin finish.

Overall Dimensions:

15.5" wide x 31.25" tall.

Installation Guide:

The Splash Guard is installed below the XLERATOR® Hand Dryer. Double-sided tape or liquid adhesive (Silicone, Mirror Adhesive) can be used to adhere onto wall. Adhesive silicone and liquid nails are not included. Please see Page 2 for a more detailed installation guide.

Warranty:

Limited 1 year warranty covers manufacturer defects. Newton Distributing Company will replace the product at no charge if defects due to manufacturing processes are shown to exist. Damage caused by improper use or care of product is the sole responsibility of the user.



Front

Laserguard Film



Back

Non-Film Side



1. Carefully remove protective film from FRONT of Splash Guard.
2. Apply adhesive or double-sided tape to BACK (non-film side) of Splash Guard and adhere to wall beneath hand dryer.



Temporary Tape



(after liquid adhesive application)

Finished Product



3. When using liquid adhesive, please secure Splash Guard temporarily with masking tape (or similar) until product cures. Once the adhesive properly sets (typically 2-4 hrs) carefully remove tape.
4. Your splash guard is installed and ready for action.